





## Support 2D Barcode Printing

### 300mm/sec ultra high print speed



- ◆ Compatible with ESC/POS and Star commands
- ◆ Waterproof, oil-proof, dust-proof structure
- ◆ Kitchen printing and network printing supported
- ◆ Network status monitoring, multilink printing supported
- ◆ OPOS driver supported
- ◆ Printer authentication and software bundle
- ◆ High speed driver printing mode, serial port speed is 66% faster
- ◆ Auto print recovering when network disconnected
- ◆ Virtual serial port for USB connection, USB port supports OPOS application
- ◆ 100MB network interface card makes the connection and print much faster, stop receipts misprinting



## Specification

<b>Print method</b>	Direct thermal line	<b>Barcode type</b>	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
<b>Dot density</b>	512dot/line, 576dot/line	<b>Character</b>	ANK character: Font A: 12x24dots Font B: 9x17dots Chinese: 24x24dots
<b>Print speed</b>	300mm/s	<b>Driver</b>	Windows2000/2003/XP/Vista/7/OPOS/Linux
<b>Interface</b>	Serial+USB+Ethernet, Parallel+USB	<b>Power supply</b>	DC 24V/2A
<b>Paper width</b>	79.5±0.5mm	<b>Reliability</b>	150KM
<b>Paper diameter</b>	83mm	<b>Fonts</b>	GB18030
<b>Paper thickness</b>	0.06~0.08mm	<b>NV Flash</b>	256K bytes
<b>Auto cutter</b>	1.5 million cuts	<b>Data buffer</b>	128K bytes
<b>Weight</b>	1.24KG	<b>Storage environment</b>	Temperature: -10~60%, Humidity: 10~90%
<b>Dimension</b>	140x175x137mm(WxLxH)		
<b>Work environment</b>	Temperature: 0~45°C, Humidity: 10~80%		